

# MNO.12 ALUMINIUM TILTING TOWER LADDER

TOOLS TRAY



HANDLE



HEAVY MS BASE




VERTICAL POSITION

HORIZONTAL POSITION

## AVAILABLE SIZES

	Closed	Extended	Max working height
2 SECTION	10ft (3.05 M)	17ft (5.18 M)	20ft (5.79 M)
	12ft (3.66 M)	21ft (6.4 M)	24ft (7.01 M)
	14ft (4.27 M)	25ft (7.62 M)	28ft (8.23 M)
	16ft (4.88 M)	29ft (8.84 M)	32ft (9.45 M)
	18ft (5.49 M)	32ft (9.76 M)	35ft (10.37 M)
	20ft (6.1 M)	35ft (10.67 M)	38ft (11.28 M)
	24ft (7.32 M)	43ft (13.11 M)	46ft (13.72 M)
3 SECTION	10ft (3.05 M)	24ft (7.32 M)	27ft (7.93 M)
	12ft (3.66 M)	30ft (9.15 M)	33ft (9.76 M)
	14ft (4.27 M)	36ft (10.98 M)	39ft (11.59 M)
	16ft (4.88 M)	40ft (12.2 M)	43ft (12.8 M)
	18ft (5.49 M)	45ft (13.72 M)	48ft (14.33 M)
	20ft (6.1 M)	50ft (15.24 M)	53ft (15.85 M)
	24ft (7.32 M)	60ft (18.29 M)	63ft (18.9 M)



**'C' SECTION SIDE RAILS**  
67mm strong side rails made up of high tensile aluminium alloy

### 1" ROUND STEPS

Corrugated steps ensures antislip surface and firm grip placed at 10"/12"



**WIREROPE AND PULLEY**  
Heavy duty wire rope and pulleys for easy tilting and extending operations

### WINCH GEAR


1 No. for extending & Retracting mechanism & 1 No. for tilting mechanisms with dual locking arrangements.



**EXTENSION LOCKING DEVICE**  
Pendulum type lock which locks the tower at every rung, provides extra safety

### PLATFORM

Large Aluminium antiskid platform of 18 x 21 inches fixed at 3 feet below from the top



**JACK AND WHEELS**  
4nos. Wheels operated by turning device for easy maneuverability and 4nos. Turn Jack for stability