

# MNO.6 ALUMINIUM SQUARE TOWER LADDER

TOOLS TRAY




HANDLE

HEAVY MS BASE


### AVAILABLE SIZES

	Closed	Extended	Max working height
2 SECTION	10ft (3.05 M)	17ft (5.18 M)	20ft (5.79 M)
	12ft (3.66 M)	21ft (6.4 M)	24ft (7.01 M)
	14ft (4.27 M)	25ft (7.62 M)	28ft (8.23 M)
	16ft (4.88 M)	29ft (8.84 M)	32ft (9.45 M)
	18ft (5.49 M)	32ft (9.76 M)	35ft (10.37 M)
	20ft (6.1 M)	35ft (10.67 M)	38ft (11.28 M)
	24ft (7.32 M)	43ft (13.11 M)	46ft (13.72 M)
3 SECTION	10ft (3.05 M)	24ft (7.32 M)	27ft (7.93 M)
	12ft (3.66 M)	30ft (9.15 M)	33ft (9.76 M)
	14ft (4.27 M)	36ft (10.98 M)	39ft (11.59 M)
	16ft (4.88 M)	40ft (12.2 M)	43ft (12.8 M)
	18ft (5.49 M)	45ft (13.72 M)	48ft (14.33 M)
	20ft (6.1 M)	50ft (15.24 M)	53ft (15.85 M)
	24ft (7.32 M)	60ft (18.29 M)	63ft (18.9 M)





**'C' SECTION SIDE RAILS**  
67mm strong side rails made up of high tensile aluminium alloy

**1" ROUND STEPS**  
Corrugated steps ensures antislip surface and firm grip placed at 10"/12"





**WIREROPE AND PULLEY**  
Heavy duty wire rope and pulleys for easy extension and retraction operations

**WINCH GEAR**  
Robust Winch gear for extending mechanism with dual locking arrangements.

**EXTENSION LOCKING DEVICE**  
Pendulum type lock which locks the tower at every rung, provides extra safety

**PLATFORM**  
Large Aluminium antiskid platform of 18 x 21 inches fixed at 3 feet below from the top




**JACK AND WHEELS**  
4nos. Wheels operated by turning device for easy maneuverability and 4nos. Turn Jack for stability